

E-flex Jet Wash Hose (1 & 2 wire)

1 Wire



Tube Oil resistant synthetic polymer
 Reinforcement: One or Two high tensile steel wire braid
 Cover: Oil Abrasion ozone and weather resistant synthetic rubber
 Colour: Black, Grey, Blue and others by request
 Temperature: -40 Degree C to +100 Degree C

Part No.	Inside Diameter		Outside Diameter	Max Working Pressure		Min Burst Pressure		Minimum Bend Radius	Weight Kg
	inch	mm		bar	psi	bar	psi		
041SS	1/4"	6.4	13.2	276	4000	828	12000	100	0.22
051SS	5/16"	8.0	14.8	276	4000	828	12000	115	0.26
061SS	3/8"	9.5	17.2	276	4000	828	12000	130	0.33
081SS	1/2"	12.7	20.4	206	3000	620	9000	180	0.41

2 Wire



Part No.	Inside Diameter		Outside Diameter	Max Working Pressure		Min Burst Pressure		Minimum Bend Radius	Weight Kg
	inch	mm		bar	psi	bar	psi		
042SS	1/4"	6.4	15.0	400	5800	1200	18000	100	0.38
052SS	5/16"	8.0	16.5	400	5800	1200	18000	115	0.43
062SS	3/8"	9.5	18.9	400	5800	1200	18000	130	0.55
082SS	1/2"	12.7	22.2	400	5800	1200	18000	180	0.64

